



Kährs®



WOOD FLOORING

A PASSION FOR PERFECTION

Kährs has firmly established itself as a global market leader in the wood flooring industry. Our passion for wood is manifested in the outstanding design, high technical performance and quality of our wood floors. Today, you can find Kährs wood floors in homes and contexts from San Francisco via Stockholm to Singapore. And although our range of floors is now extensive, covering a wide spectrum of colours, surface treatments and looks, they still all have something in common.

One of these is our focus on design. Few other design features can define or coordinate an interior as well as a carefully chosen wood floor, which has the power to lift any interior. Other common features for our wood floors include quality and innovation. Still based in the small town of Nybro, set in the deep forest of southern Sweden, a passion for perfection has been passed on from generation to generation in our company. Over the decades, we have been constantly exploring new ways of perfecting our methods of making the best, most beautiful and sustainable wood floors in the world.

Floors beyond expectations.

COVER CHEVRON DARK BROWN

STUDIO OAK CD



WHY KÄHRS ENGINEERED WOOD FLOORING



BEAUTY WITH A CONSCIENCE

When you choose a wood floor you also make a good environmental choice, both for your indoor environment and for our planet. Kährs inventions have radically changed the wood flooring industry globally - while also contributing to sustainable development.

By using wood, supporting the replanting of forests and showing consideration for the environment in every step of our processes, we do our best to ensure that our operations are conducted in a both sustainable and responsible way – and to inspire others to do the same.




WIDE RANGE OF COLOURS

Our wood floors come in many different wood species, sizes, patterns and finishes that provide endless variations and looks. Brushed, hand-scraped, bevelled, silky smooth or matt – each Kährs plank is unique and individually treated, according to its own unique composition of knots and graining and the look we want to achieve.



FAST & SAFE INSTALLATION

Kährs launched Woodloc® 5S – the evolution of the market-leading Woodloc® system, with which Kährs revolutionised the flooring industry in 2000. Kährs offers three different joint systems depending on board construction.



MULTI LAYER CONSTRUCTION

The multi-layered engineered flooring board was originally invented by Kährs. Its use and design possibilities, combined with ease of installation and long lasting beauty has made this type of wood flooring the most preferred choice globally.



REFINED SURFACES

We offer many types of surface treatments that will both enhance and protect the natural beauty of the wood. All our surface treatments are naturally free from solvents, formaldehyde and isocyanate. They also make the floor easy to clean and maintain.



UNDERFLOOR HEATING

All Kährs floors, except Beech and Hard Maple, are suitable for use with underfloor heating. If properly installed, you will achieve a beautiful and long-lasting wood floor with the increased comfort of radiating a pleasant warmth.




COMPLETE SYSTEM

We offer a complete system of flooring accessories that are designed to ensure quality in every detail of the floor, ranging from installation products to maintenance and repair products.

KÄHRS HARDWOOD RANGES



10



KÄHRS HARDWOOD

3-LAYER FLOORING

Our 3-layer floors consist of a surface layer, core layer and backing. The core material is made from pine/spruce lamella. The total thickness of the floor is 13–20 mm. The surface layer can be re-sanded 3–4 times. Our 3-layer floors can be both installed floating on a level, solid surface such as concrete, particleboard or wood with suitable underlayer material, or with glued down installation. They are quickly and easily installed with the glueless Woodloc® system and suitable for areas with light to moderate traffic.

38



KÄHRS HARDWOOD

2-LAYER FLOORING

The 2-layer floors consist of a surface layer and backing. The core material is made from pine/spruce lamella. The total thickness of the floor is 9–11 mm. The surface layer can be re-sanded 2 times. Our 2-layer floors are installed glued down with full surface bonding. They are suitable for areas with light to moderate traffic.

48



KÄHRS HARDWOOD

VENEER FLOORING

Our veneer flooring consists of three layers; surface, core and backing. The core is made from HDF and the surface from real wood. The total thickness is 7–10 mm, where 7 mm is not sandable. 10 mm has the added benefit of being sandable. The thin construction makes them perfect for renovation projects. The glueless Woodloc® joint installation system ensures fast and easy installation. These floors are suitable for areas with light traffic.

DESIGN GUIDE

Nature is wonderfully diverse. So are Kährs wood floors. The appearance depends on a number of factors, including board pattern, grading, surface treatment and refining treatment. This provides almost endless design opportunities.



 **OIL**

Oil brings out the fine structure and grain of the wood and enhances its natural color. For moderate or higher traffic areas, we recommend harder wood species – e.g. oak – treated with oil. Oiled surfaces will retain their quality and appearance, if serviced on a regular basis.



 **MATT LACQUER**

Kährs matt lacquer is as hardwearing and easy to maintain as our satin lacquer. The subtle finish produces an untreated, bare wood look. A matt surface is coarser than a satin surface.



 **ULTRA-MATT LACQUER**

Wood treated with our ultra-matt lacquer feels and looks as if it was made from untreated, newly sawn timber, but has a strong, yet silky and invisible shield against wear and tear. It creates a surface that effectively absorbs the light – enhancing both the colour and feeling of the floor. The ultra-matt surface is coarser than a matt surface.



 **SILK LACQUER**

Lacquered floors are easy to maintain. Our silk lacquer complements the wood's character by accentuating its natural structure. It also makes the floor more hardwearing and easier to clean. Despite its strength, Kährs' lacquer coating is exceptionally thin and, unlike many other lacquers, does not conceal the structure of the wood.



 **HIGH GLOSS LACQUER**

The high gloss lacquer gives your floor a shiny, polished look that enhances the beauty of the wood species you've chosen. It also protects your floor from everyday wear and tear.



 **BRUSHING**

Brushing the surface highlights the natural structure of the grain and emphasizes the texture of the wood. Brushing effects vary, depending on the wood species. Brushes are made from different materials in varying degrees of hardness, and brushing is often carried out along with other refining treatments, such as staining and bevelling of edges.



 **STAINING**

Staining offers opportunities to enhance the wood's natural colour tones. It also allows us to apply new colours, thus completely transforming the appearance of the wood. Kährs offers a wide range of stained options – from the palest white to rich charcoal shades.



 **SMOKING**

The smoking process alters the colour and shade of the plank. There are two grades of smoked finish: light and the darker fully smoked.



 **BEVELLED EDGES**

Kährs offers a number of floors with a bevelled edge finish in varying degrees, from “microbevelling” – tiny clarification and reinforcement of the edges created using sandpaper – to more prominent bevelling on both the long and the short sides, for a rustic, robust appearance. A bevelled edge feature on a 1-strip floor gives the floor a very distinct look.



 **HANDSCRAPING**

By using different tools for manual wood scraping and sanding, a new wood floor can be given a worn appearance. It takes a great amount of manual work to achieve a rustic character.

DESIGN



CALM (CITY)

These floors are produced from our cleanest boards; i.e. from planks with a uniform appearance with small variations in grain, may contain small knots.



VARIATION (TOWN)

The floors with this grading are characterized by subtle variations in colour, tone and pattern, may contain small knots.



LIVELY (COUNTRY)

The Lively floors feature dramatic graining, gnarls and knots. They boast greater colour variations and have a more lively, rustic character.



DYNAMIC


These floors are made from boards with knots and cracks that give them a both lively and dramatic, yet warm character. They feature a variety of colour tones.



EXPRESSIVE

If you want your floor to make a really strong impression, choose an Expressive floor. These are made from boards with dramatic cracks and powerful knots and with a wide variety of colour tones.

PLANK DESIGN



1-STRIP

The surface layer of every 1-strip board is sawn from a single piece of wood. The natural appearance of the wood, including knots, colour variations and grain, is reflected in this.


2-STRIP

The surface layer is two strips' wide. The strips are selected and arranged to give each 2-strip floor its own unique character.

3-STRIP


The surface layer of a 3-strip floor is created by placing three wood strips of different lengths, side by side, on each board.

PATTERN DESIGN




DUTCH PATTERN

Pattern floors can give a characteristic and sometimes dramatic expression to a room. Kährs provides ready-made Dutch and pattern boards for easy and quick installation. The boards has a unique repeating pattern with three short pieces running lengthwise separated by a perpendicular piece.



CHEVRON PATTERN

The Chevron planks are cut to ensure that each "zig" and "zag" are connected at a 45 degree angle.



HERRINGBONE

In the herringbone pattern, planks are laid in a zigzag, but stacked on top of each other to create the "point".

PATTERN FLOORING

Patterned floors give a characteristic and sometimes dramatic expression to the whole interior. Chevron, herringbone or basketweave box repeat patterns. We offer you a wide selection of pattern floors, both in terms of designs and installation methods.



DUCH PATTERN

These planks consists of multiple horizontal and vertical strips.



CHEVRON

In the chevron pattern, the two planks are angled at the end to come together to form a perfect point.



HERRINGBONE

In the herringbone pattern, planks are laid in a zigzag, but stacked on top of each other to create the "point".



REFERENCES

Kährs engineered hardwood floors have been installed in both commercial and residential areas around the world. From restaurants, hotels, shops, offices, private homes to sports facilities, schools, concert halls and theatres. Our reference cases give you an idea of our field of expertise.

Multilayer flooring references

- Asia Spa, Sweden
- B1 Lounge, Austria
- Convinium, Peru
- Craftbrew bar, England
- Resturant Cielo, Germany
- Espresso house, Sweden
- Hotel am Römerweg, Austria
- Dropbox EMEA Headquarters, Ireland
- Concert Hall Aarhus, Denmark
- Ideon at Neocon Exhibitions, USA
- Prague National Theatre, Czech Republic
- St Philips Church, England
- Haworth Castelli Creative Centre, Italy
- Liberty Towers, USA
- Volkswagen Autostadt, Germany
- Wilnecot Comprehensive School, England
- Apartments 100 West 18 th, USA
- Arriva Condominiums, Canada
- ecoTECH Organics Home, England

- Union Lofts, USA
- Victoria Park, Sweden
- Autohaus 2.0, Germany
- Clerys, Ireland
- Electrolux, Germany
- Harrods, England
- Haberdash, Sweden

Veneer flooring references


- IAA BMW, Germany
- Grand hotel Central, Spain
- Hotel Montes, Austria
- The barcode bedroom, Russia
- Fairways in the Greens, UAE
- Carlton Square, England
- Vaivai Restaurant, Germany
- Miotto Design, Italy
- Heyraud, France
- Roche Bobois Monza, Italy
- The Villa, UAE

Visit kahrsflooring.com to discover our case studies.





NOUVEAU GRAY



Hardwood layer
Pinefinger middle layer
Plywood backing layer

KÄHRS HARDWOOD 3-LAYER FLOORING


Our 3-layer floors consist of a surface layer, core layer and backing. The core material is made from pine/spruce lamella. The total thickness of the floor is 13–20 mm. The surface layer can be re-sanded 3–4 times. Our 3-layer floors can be both installed floating on a level, solid surface such as concrete, particleboard or wood with suitable underlayer material, or with glued down installation. They are quickly and easily installed with the glueless Woodloc® system and suitable for areas with light to moderate traffic.

| | |
|-----------------------------|---|
| Construction: | 3 layer construction. Surface layer, core layer and backing. |
| Thickness: | 13–20 mm |
| Resandable: | 3–4 times |
| Joint system: | Woodloc® and tongue & groove |
| Installation method: | Floating or glued down |
| Under floor heating: | Yes |
| Applications: | Light to moderate traffic |






ASH ALABASTER **A**
●



ASH AIR **B**
○



OAK SHELL **A**
●




OAK NOUVEAU BLONDE **B**
●



ASH FLOW **B**
○



OAK PALE **A**
●




OAK ESTORIL **C**
●




ASH FALSTERBO **A**
●



ASH SKAGEN **A**
●




OAK SKY **B**
○



OAK VAPOR **A**
○



OAK NOUVEAU SNOW **C**
●



OAK MENTON **A**
●



OAK PALAZZO BIANCO **D**
●



OAK PALAZZO BIONDO **D**
●

SIZE: **A** | 2423 X 200 X 15, **B** | 2420 X 187 X 15, **C** | 2266 X 187 X 15, **D** | 2426 X 198.5 X 15

● MATT LACQUER ○ ULTRA MATT LACQUER ● OIL ● SILK MATT LACQUER <<< SMOKED STAINED

BRUSHED HANDSCRAPED BEVELED MICRO BEVELED (1) (2) (3) 1, 2, 3-STRIP




OAK CIRRUS A
● 🪵 🪵




ASH CERIALE A
● 🪵




OAK GARMISCH B
🌸 🪵 🪵



OAK ABETONE A
● 🪵




OAK DEW A
🌸 🪵 🪵



OAK PORTOFINO A
● 🪵



OAK GUSTAF B
🌸 🪵 🪵



OAK OLOF B
🌸 🪵 🪵



OAK KLINTA B
🌸 🪵 🪵




OAK SORRENTO A
● 🪵




OAK NOUVEAU WHITE B
● 🪵 🪵




OAK PALLIDO B
🌸 🪵 🪵




OAK BRIGHTON, LIVELY C
● 🪵




OAK MANOR L
🌸 🪵 🪵



OAK VISTA B
🌸 🪵 🪵



OAK PARIS C
🌸 🪵 🪵 | ○ 🪵 🪵



OAK OYSTER M
🌸 🪵 🪵



OAK HORIZON B
○ 🪵 🪵


SIZE: A | 2423 X 200 X 15, B | 2420 X 187 X 15, C | 2266 X 187 X 15, L | 2800 X 260 X 20, M | 1900 X 190 X 15

● MATT LACQUER ○ ULTRA MATT LACQUER 🌸 OIL 🌿 SILK MATT LACQUER ☼ SMOKED 🪵 STAINED

🪵 BRUSHED ~ HANDSCRAPED ~ BEVELED ~ MICRO BEVELED ① ② ③ 1, 2, 3-STRIP




ASH STREAM **B**
○ 𐀀 𐀁 𐀂



OAK COAST **B**
○ 𐀀 𐀁 𐀂




OAK MIST **A**
○ 𐀀 𐀁 𐀂




OAK PRAGUE **B**
○ 𐀀 𐀁 𐀂



OAK TWILIGHT **A**
○ 𐀀 𐀁



OAK SHORE **B**
○ 𐀀 𐀁 𐀂



OAK VINGA **A**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄




OAK NOUVEAU GRAY **B**
● 𐀀 𐀁 𐀂



OAK STONE **A**
⊛ 𐀀 𐀁 𐀂 𐀃




OAK KINDA **B**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄




OAK BERLIN **C**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄




OAK INDOSSATI **M**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄




OAK HANDBÖRD **B**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄 𐀅




OAK MÖRE **B**
⊛ 𐀀 𐀁 𐀂 𐀃




OAK LINEN **M**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄 𐀅




OAK STURE **B**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄




OAK GRANITE **A**
● 𐀀 𐀁 𐀂 𐀃



OAK SPACE **X**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄



OAK CONCRETE **M**
⊛ 𐀀 𐀁 𐀂 𐀃




OAK YDRE **B**
⊛ 𐀀 𐀁 𐀂 𐀃 𐀄 𐀅



OAK NOUVEAU GREIGE **C**
● 𐀀 𐀁 𐀂 𐀃 𐀄

SIZE: **A**|2423 X 200 X 15, **B**|2420 X 187 X 15, **C**|2266 X 187 X 15, **D**|2426 X 198.5 X 15,, **L**|2800 X 260 X 20,
M|1900 X 190 X 15, **N**|2000 X 187 X 15, **O**|2419 X 196 X 15

● MATT LACQUER ○ ULTRA MATT LACQUER ⊛ OIL ⊛ SILK MATT LACQUER 𐀃 SMOKED 𐀄 STAINED
𐀀 BRUSHED 𐀁 HANDSCRAPED 𐀂 BEVELED 𐀃 MICRO BEVELED ① ② ③ 1, 2, 3-STRIP



ASH GOTHENBURG A




ASH VAILA A




ASH KALMAR A



BEECH VIBORG A




BEECH HELLERUP A




OAK LECCO A




OAK COSENZA N




OAK NICE A




OAK ERVE A




OAK DUBLIN B



OAK VERONA A



OAK DAWN A




OAK SUN B




OAK SIENA A




OAK BURGUNDY C




OAK VIENNA A




OAK HAMPSHIRE B



RED OAK NATURE A



OAK JOHAN B



OAK CORNWALL B




OAK PALAZZO ROVERE D


SIZE: A | 2423 X 200 X 15, B | 2420 X 187 X 15, C | 2266 X 187 X 15, D | 2426 X 198.5 X 15, N | 2000 X 187 X 15

● MATT LACQUER ○ ULTRA MATT LACQUER ☼ OIL ☼ SILK MATT LACQUER ☼ SMOKED ☼ STAINED


☼ BRUSHED ☼ HANDSCRAPED ☼ BEVELED ☼ MICRO BEVELED ① ② ③ 1, 2, 3-STRIP




OAK EARTH **M**
☼ 🪵 ~ 🪵 🌀 ~




OAK TRAMONTO **B**
☼ 🪵 🌀 ~




OAK FREDRIK **B**
☼ 🪵 ~ 🌀 ~




OAK SEVEDE **B**
☼ 🪵 🪵 🌀 ~ ~



OAK TERRA **B**
○ 🪵 🌀 🪵 ~




OAK SPARUTO **M**
☼ 🪵 ~ 🪵 🌀 ~



OAK ALE **A**
● 🪵 🪵




WALNUT PHILADELPHIA **A**
☼




WALNUT MONTREAL **A**
☼




OAK PALAZZO FUMO **D**
● 🌀




OAK BROWNIE **A**
● 🪵 🪵




OAK ULF **B**
☼ 🪵 ~ 🪵 ~




OAK LAVA **A**
● 🪵 🪵



OAK NOUVEAU BLACK **B**
● 🪵 🪵 ~



OAK SOIL **A**
☼ 🪵 🪵 🌀



OAK NOUVEAU TAWNY **B**
● 🪵 🪵 ~



OAK NOUVEAU CHARCOAL **A**
● 🪵 🪵 ~

SIZE: **A** | 2423 X 200 X 15, **B** | 2420 X 187 X 15, **C** | 2266 X 187 X 15, **D** | 2426 X 198.5 X 15, **M** | 1900 X 190 X 15

● MATT LACQUER ○ ULTRA MATT LACQUER ☼ OIL ☼ SILK MATT LACQUER 🌀 SMOKED 🪵 STAINED

🪵 BRUSHED ~ HANDSCRAPED ~ BEVELED ~ MICRO BEVELED ① ② ③ 1, 2, 3-STRIP







PALLIDO



STREAM





PIAZZA SMOKED OAK CD



Hardwood layer
Pinefinger middle layer

KÄHRS HARDWOOD 2-LAYER FLOORING

The 2-layer floors consist of a surface layer and backing. The core material is made from pine/spruce lamella. The total thickness of the floor is 9–11 mm. The surface layer can be re-sanded 3–4 times. Our 2-layer floors are installed glued down with full surface bonding. They are suitable for areas with light to moderate traffic.

| | |
|-----------------------------|--|
| Construction: | 2 layer construction. Surface layer and core layer. |
| Thickness: | 9–11 mm, Kährs Chevron 15mm |
| Resandable: | 2 times |
| Joint system: | Tongue & groove |
| Installation method: | Glued down with full surface bonding |
| Under floor heating: | Yes |
| Applications: | Light to moderate traffic |




OAK AB WHITE OIL J




OAK CD WHITE OIL J



OAK AB DIM WHITE OIL J



OAK CC DIM WHITE OIL J



OAK CD WHITE OILED H J



OAK AB WHITE OILED J



OAK AB WHITE MATT LACQUER J



OAK CC CREAMY WHITE OIL J



OAK CD GREY OIL J



OAK CHEVRON GREY I



OAK CHEVRON LIGHT BROWN I



OAK CHEVRON DARK BROWN I

SIZES:
I | 1848 X 305 X 15
J | 600 X 120 X 11
K | 490 X 70 X 11


- MATT LACQUER
- ULTRA MATT LACQUER
- ✿ OIL
- ☼ SILK MATT LACQUER
-))) SMOKED
- 🔪 STAINED
- 🪥 BRUSHED
- 〰 HANDSCRAPED
- 〰 BEVELED
- 〰 MICRO BEVELED
- 1 2 3 1, 2, 3-STRIP



OAK CD SMOKED OIL J



OAK AB NATURAL MATT LACQUER J



OAK AB NATURAL OILED J



OAK CD NATURAL OILED H J



AM. WALNUT AB NATURAL OILED K



AM. WALNUT AB MATT LACQUER K



SMOKED OAK AB OILED K



SMOKED OAK AB MATT K





ATELIER SMOKED OAK AB



ATELIER OAK AB WHITE E



ATELIER OAK CD E



ATELIER SMOKED OAK AB E



STUDIO OAK CC WHITE F



STUDIO OAK CC GREY G



STUDIO OAK CD NATURAL OILED F



PIAZZA OAK AB H



PIAZZA SMOKED OAK CD GREY H




PIAZZA SMOKED OAK CD H

SIZES: E|1200 X 120 X 11, F|490 X 70 X 9, G|490 X 70 X 11, H|1800 X 180 X 11

● MATT LACQUER ○ ULTRA MATT LACQUER ☼ OIL ☼ SILK MATT LACQUER ☼ SMOKED 🪵 STAINED
🪵 BRUSHED ~ HANDSCRAPED ~ BEVELED ~ MICRO BEVELED ① ② ③ 1, 2, 3-STRIP







KÄHRS HARDWOOD VENEER FLOORING

Our veneer flooring consists of three layers; surface, core and backing. The core is made from HDF and the surface from real wood. The total thickness is 7-10 mm. 7 mm should not be sanded, whereas 10 mm can be sanded one time. The thin construction makes them perfect for renovation projects. The glueless Woodloc® joint installation system ensures fast and easy installation. These floors are suitable for areas with light traffic.


| | |
|-----------------------------|---|
| Construction: | 3 layer construction. Surface layer, core layer and backing. |
| Thickness: | 7-10 mm |
| Resandable: | No |
| Joint system. | Woodloc® |
| Installation method: | Floating or glue down |
| Under floor heating: | Yes |
| Applications: | Light traffic |




ASH BLIZZARD **M**
● 🪵 ~



OAK DOME **L**
● 🪵 ~




ARCTIC OAK **N**
● 🪵 ~



OAK POWDER **N**
● 🪵 ~




OAK COLONY **L**
● 🪵 ~




OAK TIDE **M**
● 🪵



HARD MAPLE SUMMER **M**
●




OAK TOWER **L**
● 🪵 ~




CHERRY WINTER **M**
●




OAK BREEZE **M**
● | ●




REEF OAK **N**
● 🪵 ~




PARK OAK **N**
● 🪵 ~




OAK VILLAGE **L**
● 🪵 ~




OAK ROCK **N**
● 🪵 ~




OAK OUTPOST **L**
● 🪵 ~




WALNUT BLOOM **M**
●




WALNUT STATUE **L**
● ~




GARDEN WALNUT **N**
● ~




HARBOR OAK **N**
● ~



OAK GATE **L**
● 🪵 ~



ORCHARD WALNUT **N**
● ~



OAK CASTLE **L**
● 🪵 ~

SIZE: **L** | 1810 X 150 X 7, **M** | 1225 X 193 X 7, **N** | 1830 X 125 X 10

● MATT LACQUER ● OIL ● SILK MATT LACQUER ~ SMOKED 🪵 STAINED
🪵 BRUSHED ~ MICRO BEVELED ① ② ③ 1, 2, 3-STRIP





TOWER



DOME

A COMPLETE SYSTEM



STAIR NOSE




COVER STRIP




FINNISH PROFILE



SKIRTINGS



SKIRTINGS



COVER STRIP



Kährs offers a complete flooring system where every detail – from the skirtings to the wide range of installation and maintenance products – has been design to enhance the beauty of strength of the floor.

THE PERFECT FINISH

The smallest things often make the biggest difference. This is true of a Kährs floor, where the highest level of skill and craftsmanship is added to every detail, including the skirting boards and different types of mouldings.

CARE AND MAINTENANCE

Kährs Care and Maintenance range covers all you need for daily care as well as regular maintenance of the floor. It also includes products for a damaged floor.

SERVICES

At kahrsflooring.com you will find more information – and inspiration – about our floors, our company and the environment. The Kährs website is a helpful tool to you in your professional capacity. For additional information and consultation, please contact your local Kährs representative.


DOCUMENTS FOR DOWNLOADING

At kahrsflooring.com you will find a number of documents for downloading, containing facts about our different types of wood and vinyl flooring. These include technical data sheets, design guides, features, technical information, installation and maintenance guides.

ORDER SAMPLES

Kährs offers flooring samples to architects and designers free of charge. You can order a maximum of 3 samples at a time.

The delivery usually takes 3–5 working days after we have processed your order. Please note that your order may come in separate deliveries depending on where the products are stocked.



ENVIRONMENTAL INFORMATION

You will find a substantial amount of information relating to our products, environmental policies and our latest environmental reports gathered on kahrsflooring.com.



BIM AND CAD OBJECTS

By offering BIM objects on our global assortment of hardwood we give you, as an architect and designer, the possibility to easily incorporate our products in your project planning, visualizing ideas and optimizing the result of the project.

At our website kahrsflooring.com you can search and filter our wide range of hardwood floors, and on each product page you can easily access and download our BIM objects or CAD textures. We also provide access to our BIM files on bimobjects.com.



SHOWROOMS AROUND THE WORLD

Our global network of showrooms provides the required infrastructure for commercial project processes around the world. They support architects and designers, while ensuring that our floors are professionally delivered and installed. Today, our showrooms can be found in design metropolises around the world, including Stockholm, London, Shanghai, Dubai, Moscow and Madrid.

KÄHRS

Kährs is a world-leading flooring manufacturer in hardwood and resilient flooring with a number of strong brands in its product portfolio. The company is dedicated to providing the market with innovative new flooring solutions.

Kährs Group, which delivers products to more than 70 countries, is the market leader in Sweden, Finland, Norway and Russia and holds a strong position in other markets, such as the UK and Germany.

Colour reproduction within the brochure cannot be guaranteed, due to limitations in print technology. We, therefore, recommend that you visit your local Kährs dealers to ascertain a better representation of the products.





www.jular.pt

Sede e Fábrica:

Estrada Nacional 3, Km. 5,9
Vila Nova da Rainha
P-2050-522 Azambuja

Tel.: 263 850 070
Tlm.: 919 999 960

azambuja@jular.pt

Lisboa:

Rua das Oliveiras, 42 - Apt. 1042
Quinta de Santa Rosa
P-2681-901 Camarate

Tel.: 219 484 000
Tlm.: 919 999 666

mail@jular.pt

Norte:

Rua Oriental, 573
Apt. 5069
P-4456-901 Perafita

Tel.: 229 953 638
Tlm.: 919 550 654

porto@jular.pt

Centro:

Estrada da Atouguia
P-2495-651 Fátima

Tel.: 249 531 879
Tlm.: 916 896 001

fatima@jular.pt

Sul:

Urb. Serva, Bloco 1-A
Vale Paraíso
P-8200-567 Albufeira

Tel.: 289 588 538
Tlm.: 916 895 885

algarve@jular.pt



Kährs®

FLOORS BEYOND EXPECTATIONS

www.kahr flooring.com